

Land Levellers

LL5

- Fully galvanised
- For horticultural and parkland use
- Reversible head stock for option of smooth pass
- 3 aggressive blades and 1 reversed for smooth finish
- Cat 1 pins
- Four 60mm X 60mm by 6mm blades
- 20–30hp



Model	LL5
Reversible	Yes
Width	1.5m
Length	0.9m
Weight	70kg
HP	20
Lift pins facility	Cat .1
Rigid/Folding	Rigid

LL8

- Galvanised headstock support
- Double jaw lift arm support
- 3 aggressive blades and 1 reversed for smooth finish
- Four 80mm x 80mm by 8mm blades
- Reversible galvanised head stock
- 35–75hp
- Cat 2 lift pins



Model	LL8
Reversible	Yes
Width	2.4m
Length	1.53m
Weight	150kg
HP	35
Lift pins facility	Cat 2
Rigid/Folding	Rigid



Land Levellers

LL10



- Four 80mm X 80mm by 10mm blades
- 3 aggressive blades and 1 reversed blade for smooth finish
- Reversible galvanised head stock
- Double jaw lift arm support
- Galvanised headstock support
- Reinforced HD frame
- Cat 2 lift pins
- 75-95hp

Model	LL10
Reversible	Yes
Width	3m
Length	1.53m
Weight	250kg
HP	75
Lift pins facility	Cat 2
Rigid/Folding	Rigid

LL12



- Ideal for contracting and land reclamation
- Raised reinforcing cross bar to allow free flow of material
- Double jaw support for lift arm pins
- 3 aggressive blades and 1 reversed for smooth final pass
- Four 80mm X 80mm by 10mm blades
- Heavy duty construction
- Heavy duty rams
- 100+ hp
- 4m working mode
- 2.5m transport mode
- Cat 2 lift pins

Model	LL12
Reversible	No
Width	4m
Length	1.5m
Weight	900kg
HP	100+
Lift pins facility	Cat 2
Rigid/Folding	Folding